

RIO GRANDE BASIN		USES				CRITERIA						
		Recreation	Aquatic Life	Domestic Water Supply	Other	Cl ⁻¹ (mg/L)	SO ₄ ⁻² (mg/L)	TDS (mg/L)	Dissolved Oxygen (mg/L)	pH Range (SU)	Indicator Bacteria ¹ #/100ml	Temperature (°F)
Segment No.	SEGMENT NAME											
2301	Rio Grande Tidal	CR	E						5.0	6.5-9.0	35/200	95
2302	Rio Grande Below Falcon Reservoir	CR	H	PS		270	350	880	5.0	6.5-9.0	126/200	90
2303	International Falcon Reservoir	CR	H	PS		200	300	1,000	5.0	6.5-9.0	126/200	93
2304	Rio Grande Below Amistad Reservoir	CR	H	PS		200	300	1,000	5.0	6.5-9.0	126/200	95
2305	International Amistad Reservoir	CR	H	PS		150	270	800	5.0	6.5-9.0	126/200	88
2306	Rio Grande Above Amistad Reservoir	CR	H	PS		300	570	1,550	5.0	6.5-9.0	126/200	93
2307	Rio Grande Below Riverside Diversion Dam	CR	H	PS		300	550	1,500	5.0 ²	6.5-9.0	126/200	93
2308	Rio Grande Below International Dam	NCR	L	PS		250	450	1,400	3.0	6.5-9.0	605/2,000	95
2309	Devils River	CR	E	PS		50	50	300	6.0	6.5-9.0	126/200	90
2310	Lower Pecos River	CR	H	PS		1,700	1,000	4,000	5.0	6.5-9.0	126/200	92
2311	Upper Pecos River	CR	H			7,000	3,500	15,000	5.0	6.5-9.0	126/200	92
2312	Red Bluff Reservoir	CR	H			3,200	2,200	9,400	5.0	6.5-9.0	126/200	90
2313	San Felipe Creek	CR	H	PS		50	50	400	5.0	6.5-9.0	126/200	90
2314	Rio Grande Above International Dam	CR	H	PS		340	600	1,800	5.0	6.5-9.0	126/200	92

¹ The indicator bacteria for freshwater is *E. coli* and Enterococci for saltwater. Fecal coliform is an alternative indicator.

² The dissolved oxygen criterion in the upper reach of Segment 2307 (Riverside Diversion Dam to the end of the rectified channel below Fort Quitman) shall be 3.0 mg/L when headwater flow over the Riverside Diversion Dam is less than 35 ft³/s.